



**VC Systems**

|   |                                      |
|---|--------------------------------------|
| A | HEADER - 304 STAINLESS PIPE, FLANGED |
| B | ISOLATION VALVE, FULL LUG            |
| C | CHECK VALVE, FLANGED                 |
| D | PUMP - VC ES SERIES - DI / SS FITTED |
| E | MOTOR                                |
| F | CONTROL PANEL - UL 508A LISTED       |
| G | VARIABLE FREQUENCY DRIVE             |
| H | CHANNEL STEEL BASE                   |

| KEY | HEADER | ESTIMATED WEIGHT | W   | X   | Y   | Z   | Notes:  |
|-----|--------|------------------|-----|-----|-----|-----|---|
| 1   | 3"     | 1100 LBS         | 60" | 60" | 34" | 60" | 1. Not to be used for construction. Dimensions may vary. See factory for construction drawing.<br>2. Provide 18" clearance around the system for service and NEC clearance in front of control panel.<br>3. Headers are double ended for flow in either direction and fully supported from system base. |
| 2   | 4"     | 1300 LBS         | 60" | 60" | 34" | 60" |   |
| 3   | 6"     | 1500 LBS         | 60" | 60" | 36" | 60" |   |
| 4   | 8"     | 1800 LBS         | 60" | 60" | 40" | 60" |   |
| 5   |        |                  |     |     |     |     |   |

3H-8B-625